



GEESTONE

THE ULTIMATE GRIP



 Off The Road (OTR) Tyres

 Agricultural Tyres

 Ultra Light Truck Tyres

 Jeep & Van Tyres

 Skidsteer & Dumper Tyres

 Flotation Implement Tyres

 Industrial Tyres

 Tuk Tuk-4.00-8 Tyres

 Butyl Tubes

 Light Truck Tyres

 Two Wheeler Tyres

 Bicycle Tyres & Tubes

 Golf & Go-kart Tyres

 Three Wheeler Tyres

 Farm Implement Tyres



Company Profile



Incorporated in the year 1980, we, "**GEESTONE TYRES**" (PROP. RAVI NANDAN & SONS), are known as the leading manufacturer, exporter and supplier of comprehensive assortment of various types of **TYRES, TUBES & COMPONENTS**. These are manufactured using optimum quality factor inputs and sophisticated technology at par with the international standards and norms. Owing to the dedicated and combined efforts of Mr. Naresh Aul (Group Chairman), Mr. Naveen Aul (C.E.O.) and the team members, the company has been able to carve a niche for itself both in the domestic and international market. Clients can avail the entire range from us in varied specifications as per their various requirements.

Backed by highly talented and efficient team of experts, we are able to meet the ever-growing demands of the clients. We have our own well-established infrastructure, which assists us in manufacturing the finest quality range of products. Our quality inspectors check and maintain quality throughout the production process at every stage right from the selection of raw material till the final dispatch. In addition to this, our ethical business practices, fair business dealings and client-centric approach have helped us in reaching great heights of success in this domain. For meeting the diverse demands of clients in a timely manner, our staff works in close coordination and with full dedication. Due to their features such as unmatched quality, superior finish, tear and wear resistance and efficient performance, these are highly acclaimed among clients and our firm has attained a lot of admiration and clients' support.

Awards Winner



ISO 9001:2015



www.geestonetires.com

AGRICULTURAL TRACTOR FRONT TYRES



GS 51



GS 52



GS 53



GS 54



GS 55



GS 56

*AVAILABLE IN VARIOUS PLY RATINGS AS PER INTERNATIONAL STANDARDS.

SPECIFICATIONS

Size	Pattern	Ply Rating	Rim Width	Inflated Dimensions +/-2%		Load Capacity (Kg)	LP (Bar)
				OD (mm)	CSW (mm)		
4.00-4	51	4PR	3.00	323	114	155	
4.00-8	51	6PR	3.00	425	114	Free Rolling 290 Drive Wheel 206	4.25
5.00-10	51	4PR	4.00	505	145	375	2.20
5.00-12	52	6PR	4.00	545	127	220	2.40
6.00-12	52	4PR	4.00	633	164	325	2.00
5.20-14	53	8PR	4.00	620	125	220	2.40
5.50-16	53	6PR	4.00	710	150	530	3.70
6.00-16	53	8PR	4.50	735	165	675	4.50
5.50-16	54	6PR	4.00	710	150	530	3.70
6.00-16	54	8PR	4.50	735	165	675	4.50
6.50-20	54	8PR	5.00	868	180	850	4.50
7.50-16	54	8PR	5.50	805	205	875	3.70
4.00-19	55	4PR	3.00	712	112	355	3.60
5.00-15	55	4PR	4.00	545	127	220	2.40
5.50-16	55	6PR	4.00	710	150	530	3.70
6.00-16	55	8PR	4.50	735	165	675	4.50
6.00-19	55	8PR	4.00	815	160	640	3.25
7.50-18	55	8PR	5.50	860	205	950	3.70
7.50-16	55	8PR	5.50	805	205	875	3.70
7.50-20	55	8PR	5.50	915	205	1030	3.40
9.00-16	55	10PR	6.00	855	234	1250	3.90
1000-16SL	55	10PR	8.00	894	274	1360	3.40
1100-16SL	55	10PR	10.00	967	315	1500	2.80
6.00-16	56	8PR	4.50	735	165	675	4.50
7.50-16	56	8PR	5.50	805	205	875	3.70
7.50-18	56	8PR	5.50	860	205	950	3.70
8.00-18	56	4PR, 6PR	W7	835	206	515	1.60

AGRICULTURAL TRACTOR FRONT TYRES



GS 57



GS 58



GS 59



GS 60



GS 61



GS 62



GS 63

***AVAILABLE IN VARIOUS PLY RATINGS AS PER INTERNATIONAL STANDARDS.**

SPECIFICATIONS

Size	Pattern	Ply Rating	Rim Width	Inflated Dimensions +/-2%		Load Capacity (Kg)	LP (Bar)
				OD (mm)	CSW (mm)		
6.00-16	57	8PR	4.50	735	165	675	4.50
4.50-12	58	6PR	3.50	529	122	257	2.10
5.50-16	58	6PR	4.00	710	150	530	3.70
6.00-16	58	8PR	4.50	735	165	675	4.50
6.50-20	58	8PR	5.00	868	180	850	4.50
6.50-20	59	8PR	5.00	868	180	850	4.50
5.50-16	60	6PR	4.00	710	150	530	3.70
6.00-16	60	8PR	4.50	735	165	676	4.50
6.50-20	60	8PR	5.00	868	180	850	4.50
7.50-16	61	8PR	5.50	805	205	875	3.70
6.00-16	62	8PR	4.50	735	165	675	4.50
1000-16SL	63	8PR	4.50	735	165	675	4.50
1100-16SL	63	8PR	5.00	868	180	850	4.50

AGRICULTURAL TRACTOR REAR TYRES



GS 81



GS 82



GS 83

*AVAILABLE IN VARIOUS PLY RATINGS AS PER INTERNATIONAL STANDARDS.

SPECIFICATIONS

Size	Pattern	Ply Rating	Rim Width	Inflated Dimensions +/-2%		Load Capacity (Kg)	LP (Bar)
				OD (mm)	CSW (mm)		
11.2-24	81	8PR	10	1105	284	1250	2.4
12.4-24	81	8PR	11	1160	315	1450	2.3
12.4-28	81	12PR	11	1260	315	1650	2.5
13.6-28	81	12PR	12	1310	345	1800	2.3
14.9-26	81	8PR	13	1295	378	1750	1.6
14.9-24	81	8PR	13	1265	378	1800	1.8
14.9-28	81	8PR	13	1365	378	1900	1.8
18.4-26	81	12PR	16	1450	467	3000	2.3
16.9-34	81	10PR	15	1585	429	2650	2.0
18.4-34	81	10PR	16	1654	467	2650	1.40
18.4-38	81	8PR	W16	1760	467	2725	1.40
8.00-18	81	4PR	W7	835	206	515	1.60
8.3-20	81	6PR	W7	890	211	710	2.40
16.0/70-20	81	14PR	14	1097	418	Free Rolling 3750 Drive Wheel 2650	3.50
405/70-20	81	14PR	14	1097	418	Free Rolling 3750 Drive Wheel 2650	3.50
12.4-28	82	12PR	11.00	1260	315	1650	2.50
11.2-28	82	6PR	10.00	1205	284	1120	1.80
8.3-24	82	6PR	W7	995	211	825	2.40
9.5-24	82	8PR	W8	1050	241	1120	2.80
12.4-28	83	12PR	11.00	1260	315	1650	2.50
13.6-28	83	12PR	12.00	1310	345	1850	2.40
14.9-28	83	12PR	13.00	1365	378	2180	2.30
16.9-28	83	12PR	15.00	1435	429	2725	2.60
16.9-30	83	12PR	15.00	1485	429	2800	2.40
18.4-30	83	12PR	16.00	1550	467	3250	2.30

AGRICULTURAL TRACTOR REAR TYRES



GS 84



GS 85



GS 86

***AVAILABLE IN VARIOUS PLY RATINGS AS PER INTERNATIONAL STANDARDS.**

SPECIFICATIONS

Size	Pattern	Ply Rating	Rim Width	Inflated Dimensions +/-2%		Load Capacity (Kg)	LP (Bar)
				OD (mm)	CSW (mm)		
16.9-28	84	12PR	15.00	1410	429	3550	2.60
15.5/80-24	85	14PR	13.00	1262	394	Free Rolling 4500 Drive Wheel 3150	3.50
16.0/70-20	86 (HW-80)	14PR	14.00	1097	418	Free Rolling 3750 Drive Wheel 2650	3.50



AGRICULTURAL IMPLEMENT TYRES (I-I)



GS 116



GS 117



GS 118

***AVAILABLE IN VARIOUS PLY RATINGS AS PER INTERNATIONAL STANDARDS.**

SPECIFICATIONS

Size	Pattern	Ply Rating	Rim Width	Inflated Dimensions +/-2%		Load Capacity (Kg)	LP (Bar)
				OD (mm)	CSW (mm)		
9.5L-14SL	116	8PR	7.00	741	241	1090	3.00
9.5L-15SL	116	8PR	7.00	782	241	1120	3.00
11L-14SL	117	8PR	8.00	752	279	924	2.00
11L-15SL	117	8PR	8.00	777	279	1150	2.50
11L-16SL	117	8PR	8.00	803	279	1215	2.50
12.5L-15SL	117	8PR	10.00	823	318	1360	2.50
12.5L-16SL	117	8PR	10.00	848	318	1400	2.50
16.5L-16.1SL	117	8PR	14.00	1024	419	2000	2.00
10.00-15SL	118	12PR	8.00	853	275	1800	3.50



AGRICULTURAL IMPLEMENT TYRES (NON TRACTION)



GS 121



GS 122



GS 123



GS 124



GS 125

***AVAILABLE IN VARIOUS PLY RATINGS AS PER INTERNATIONAL STANDARDS.**

SPECIFICATIONS

Size	Pattern	Ply Rating	Rim Width	Inflated Dimensions +/-2%		Load Capacity (Kg)	LP (Bar)
				OD (mm)	CSW (mm)		
10.0/75-15.3	121	8PR	9.00	760	264	1360	3.10
11.5/80-15.3	121	8PR	9.00	845	290	1700	2.70
12.5/80-15.3	121	14PR	9.00	889	307	2650	4.30
12.5/80-18	121	14PR	9.00	965	308	3000	4.30
7.00-12	121	6PR	5.50	667	200	Free Rolling 690Drive Wheel 487	2.50
10.0/80-12	121	8PR	9.00	710	264	Free Rolling 1250Drive Wheel 875	3.10
13.0/65-18	122, 123	14PR	11.00	890	336	2575	4.30
10.5/65-16	122, 124	14PR	9.00	755	274	Free Rolling 1950 Drive Wheel 1320	5.30
400/60-15.5	125	8PR	13.00	874	400	Free Rolling 2120 Drive Wheel 1500	2.40

AGRICULTURAL IMPLEMENT TYRES (TRACTION)



GS 130



GS 131



GS 132

***AVAILABLE IN VARIOUS PLY RATINGS AS PER INTERNATIONAL STANDARDS.**

SPECIFICATIONS

Size	Pattern	Ply Rating	Rim Width	Inflated Dimensions +/-2%		Load Capacity (Kg)	LP (Bar)
				OD (mm)	CSW (mm)		
6.50/80-12	130	6PR	5.00	588	163	Free Rolling 650 Drive Wheel 450	3.60
10.0/75-15.3	131	12PR	9.00	780	264	Free Rolling 1700 Drive Wheel 1180	4.70
11.5/80-15.3	131	12PR	9.00	867	290	Free Rolling 2180 Drive Wheel 1550	4.10
400/60-15.5	132	8PR	13.00	874	400	Free Rolling 2520 Drive Wheel 1900	2.40



AGRICULTURAL IRRIGATION TYRES



GS I- 1



GS I- 2

***AVAILABLE IN VARIOUS PLY RATINGS AS PER INTERNATIONAL STANDARDS**

SPECIFICATIONS

Size	Pattern	Ply Rating	Rim Width	Inflated Dimensions +/-2%		Load Capacity (Kg)	LP (Bar)
				OD (mm)	CSW (mm)		
14.9-24	I-1	8PR	13.00	1265	378	1800	1.80
14.9-24	I-2	8PR	13.00	1365	378	1900	1.80

AGRICULTURAL TRACTOR TRAILER TYRES



GS 71



GS 72



GS 73

***AVAILABLE IN VARIOUS PLY RATINGS AS PER INTERNATIONAL STANDARDS**

SPECIFICATIONS

Size	Pattern	Ply Rating	Rim Width	Inflated Dimensions +/-2%		Load Capacity (Kg)	LP (Bar)
				OD (mm)	CSW (mm)		
7.50-16	71	12PR	6.00	813	211	1700	5.85
900-16	72 & 73	16PR	6.5H	912	248	2300	7.25

OFF THE ROAD (OTR) TYRES (GRADER TYRES)



GS 101

***AVAILABLE IN VARIOUS PLY RATINGS AS PER INTERNATIONAL STANDARDS.
SPECIFICATIONS**

Size	Pattern	Ply Rating	Rim Width	Inflated Dimensions +/-2%		Load Capacity (Kg)	LP (Bar)
				OD (mm)	CSW (mm)		
13.00-24	101	12 PR	8	1278	333	2725	3.00
13.00-24	101	14 PR	8	1278	333	2995	3.00
14.00-24	101	14 PR	10	1348	362	3075	2.75
14.00-24	101	16 PR	10	1348	362	3655	2.75



(OTR TYRES) (EARTHMOVER TYRES)



GS 102



GS 103

***AVAILABLE IN VARIOUS PLY RATINGS AS PER INTERNATIONAL STANDARDS**

SPECIFICATIONS

Size	Pattern	Ply Rating	Rim Width	Inflated Dimensions +/-2%		Load Capacity (Kg)	LP (Bar)
				OD (mm)	CSW (mm)		
15.5-25	102	20PR	12.00	1285	573	5600 @ 10km/h	4.00
17.5-25	102	20PR	14.00	1348	445	7300 @ 10km/h/4250 @ 50km/h	4.75/3.00
20.5-25	102	24PR	17.00/2.0	1493	521	6000 @ 50 km/h	3.25
23.5-25	102	28PR	19.5/2.5	1617	597	7300 @ 10km/h	3.00
14.00-24	102	28PR	10.00	1368	375	9500 @ 10km/h/5150 @ 50km/h	8.50/5.75
14.00-25	102	28PR	10.00	1368	375	9500 @ 10km/h/5150 @ 50km/h	8.50/5.75
12.00-24	103	20PR	8.5/1.3	1247	315	6900 @ 10km/h/3750 @ 50km/h	8.25/5.50
13.00-24	103	20PR	10.00/1.5	1301	351	7200 @ 10km/h/4050 @ 50km/h	8.50/3.00
14.00-24	103	28PR	10.00	1345	365	10000 @ 10km/h	9.25
14.00-25	103	28PR	10.00	1410	410	10000 @ 10km/h	9.25



OFF THE ROAD (OTR) TYRES (ALL TRACTION)



GS 104 (R4)

***AVAILABLE IN VARIOUS PLY RATINGS AS PER INTERNATIONAL STANDARDS**

SPECIFICATIONS

Size	Pattern	Ply Rating	Rim Width	Inflated Dimensions +/-2%		Load Capacity (Kg)	LP (Bar)
				OD (mm)	CSW (mm)		
17.5L-24	104	10PR	15.00	1241	445	2900	2.20
19.5L-24	104	12PR	17.00	1314	495	3450	2.30
16.9-24	104	10PR	15.00	1310	440	2900	2.20
16.9-28	104	16PR	15.00	1410	440	3655	3.00

FLOTATION IMPLEMENT TYRES



GS 137



GS 138

***AVAILABLE IN VARIOUS PLY RATINGS AS PER INTERNATIONAL STANDARDS**

SPECIFICATIONS

Size	Pattern	Ply Rating	Rim Width	Inflated Dimensions +/-2%		Load Capacity (Kg)	LP (Bar)
				OD (mm)	CSW (mm)		
400/60-22.5	137	16PR	11.75	1070	400	Free Rolling 4000 Drive Wheel 2880	3.50
550/45-22.5	137	16PR	16.00	1070	550	Free Rolling 4375 Drive Wheel 3075	2.80
500/50-22.5	137	16PR	16.00	1070	500	Free Rolling 4250 Drive Wheel 3000	3.00
600/50-22.5	138	16PR	18.00	1200	600	Free Rolling 4500 Drive Wheel 3150	3.50

GRADER & BACKHOE LOADER TYRES



GS 105

***AVAILABLE IN VARIOUS PLY RATINGS AS PER INTERNATIONAL STANDARDS**

SPECIFICATIONS

Size	Pattern	Ply Rating	Rim Width	Inflated Dimensions +/-2%		Load Capacity (Kg)	LP (Bar)
				OD (mm)	CSW (mm)		
12.5/70-16	105	14PR	10.00	853	315	1650 @ 40 km/h	2.7
15.5/60-18	105	14PR	13.00	950	401	2400 @ 40 km/h	2.6
15.5/70-18	105	10PR	13.00	1031	401	2650 @ 40 km/h	2.6
17.5/65-20	105	14PR	14.00	1031	450	3200 @ 40 km/h	2.4
16.9-24	105	16PR	15.00	1303	450	3900 @ 40 km/h	3.3
16.9-28	105	12PR	15.00	1410	450	3550 @ 40 km/h	2.6



INDUSTRIAL TYRES (FORKLIFT)



GS 91



GS 92



GS 93

***AVAILABLE IN VARIOUS PLY RATINGS AS PER INTERNATIONAL STANDARDS**

SPECIFICATIONS

Size	Pattern	Ply Rating	Rim Width	Inflated Dimensions +/-2%		Load Capacity (Kg)	LP (Bar)
				OD (mm)	CSW (mm)		
5.00-8	91	10PR	3.00	467	132	1090	10.00
6.00-9	91	12PR	4.00	540	160	1320	8.50
6.50-10	91	12PR	5.00	588	177	1650	9.00
7.00-12	91	14PR	5.00	672	192	2120	9.00
6.00-9	92	12PR	4.00	540	160	1320	8.50
7.50-10	92	12PR	5.50	648	208	2060	8.00
7.00-12	92	14PR	5.00	672	192	2120	9.00
6.50-10	93	12PR	5.00	588	177	1650	9.00
7.00-12	93	14PR	5.00	672	192	2120	9.00
8.25-15	93	16PR	6.50	836	234	3550	9.25



INDUSTRIAL TYRES (FORKLIFT)



GS 94



GS 95



GS 96

***AVAILABLE IN VARIOUS PLY RATINGS AS PER INTERNATIONAL STANDARDS**

SPECIFICATIONS

Size	Pattern	Ply Rating	Rim Width	Inflated Dimensions +/-2%		Load Capacity (Kg)	LP (Bar)
				OD (mm)	CSW (mm)		
7.00-15	94	12PR	5.50	750	200	2360	8.25
7.50-15	94	14PR	6.00	772	212	2800	9.25
28x9-15/8.15-15	94	14PR	7.00	707	216	3000	10.00
250-15	95	18PR	7.50	735	250	3650	9.50
300-15	95	14PR	18PR	8.00	840	300	4.50
7.00-12	96 (SMOOTH)	14PR	5.00	672	192	2120	9.00



SKIDSTEER, DUMPER & MPT TYRES



GS 111



GS 112



GS 113

***AVAILABLE IN VARIOUS PLY RATINGS AS PER INTERNATIONAL STANDARDS**

SPECIFICATIONS

Size	Pattern	Ply Rating	Rim Width	Inflated Dimensions +/-2%		Load Capacity (Kg)	LP (Bar)
				OD (mm)	CSW (mm)		
10-16.5NHS	111	10PR	8.25	774	264	2140 @ 8km/hr	5.20
12-16.5NHS	111	12PR	9.75	831	307	2765 @ 8km/hr	5.20
10.5/80-18	112	10PR	9.00	907	274	1950 Free Rolling 1360 Drive Wheel	3.70
12.5/80-18	112	12PR	9.00	980	282	2650	3.70
10-16.5	113	12PR	8.25	790	267	2360 @ 10 km/hr	6.20
12-16.5	113	14PR	9.75	850	325	3075 @ 10 km/hr	6.20



GOLF & GO-CART TYRES



GS 145



GS 146



GS 147



GS 148

***AVAILABLE IN VARIOUS PLY RATINGS AS PER INTERNATIONAL STANDARDS**

SPECIFICATIONS

Size	Pattern	Ply Rating	Rim Width	Inflated Dimensions +/-2%		Load Capacity (Kg)	LP (Bar)
				OD (mm)	CSW (mm)		
18x8.5-8	145 & 146	6PR	7.00	450	213	475	2.3
10x4.5 -5	147	-	4.00	255	115	-	4.1
11x7.1 -5	148	-	7.00	275	180	-	4.0



JEEP & VAN TYRES



GS 3



GS 61



GS 62



GS 63



GS 64



GS 65



GS 66



GS 67



GS 68



GS 69



GS 70A



GS 70B

***AVAILABLE IN VARIOUS PLY RATINGS AS PER INTERNATIONAL STANDARDS**

SPECIFICATIONS

Size	Pattern	Ply Rating	Rim Width	Inflated Dimensions +/-2%		Load Capacity (Kg)	LP (Bar)
				OD (mm)	CSW (mm)		
6.00-16	61, 62, 63, 64	8PR	4.50	731	166	710	4.15
6.50-16	3 & 65	8PR	4.50	750	175	860	4.15
6.00-14	66, 67	8PR	4.50J	678	166	750	4.25
6.50-14	66, 67, 68	8PR 10PR	4.50J	702	175	840 930	4.25
6.40-15	62	8PR	4.50J	705	160	710	4.15
6.70-15	62, 69	8PR	4.50J	715	187	820	4.15
F.78-15	70A, 70B	8PR	5.5	699	196	835	4.15

SCOOTER TYRES



GS 21



GS 22



GS 23



GS 24

***AVAILABLE IN VARIOUS PLY RATINGS AS PER INTERNATIONAL STANDARDS**

SPECIFICATIONS

Size	Pattern	Ply Rating	Rim Width	Inflated Dimensions +/-2%		Load Capacity (Kg)	LP (Bar)
				OD (mm)	CSW (mm)		
3.50-10	21	6PR	2.50	447	92	206	2.50
3.50-10	22	6PR	2.50	447	92	206	2.50
3.50-10	23	6PR	2.50	447	92	206	2.50
3.50-10	24	6PR	2.50	447	92	206	2.50



MOTORCYCLE TYRES



GS 30



GS 31



GS 32



GS 33



GS 34



GS 35



GS 36



GS 37



GS 38



GS 39

*AVAILABLE IN VARIOUS PLY RATINGS AS PER INTERNATIONAL STANDARDS

SPECIFICATIONS

Size	Pattern	Ply Rating	Rim Width	Inflated Dimensions +/-2%		Load Capacity (Kg)	LP (Bar)
				OD (mm)	CSW (mm)		
2.50-16	36	6PR	1.85	545	68	150	2.80
3.50-16	39	6PR	2.15	605	92	243	2.80
3.00-17	30, 31, 32, 33	6PR	1.85	625	81	190	2.80
3.00-18	30, 31, 32, 33, 34	6PR	1.85	625	81	200	2.80
2.75-17	34	6PR	1.85	568	76	150	2.80
2.75-18	34, 35	6PR	1.85	614	77	160	2.80
3.25-18	37, 38	6PR	2.15	635	82	250	2.80
3.50-18	37, 38	6PR	2.15	645	82	250	2.80
100/90-17	38	6PR	2.50	612	101	218	2.25
100/90-18	38	6PR	2.50	641	102	224	2.25

MOTORCYCLE TYRES



GS 38



GS 41



GS 42



GS 43



GS 44

***AVAILABLE IN VARIOUS PLY RATINGS AS PER INTERNATIONAL STANDARDS**

SPECIFICATIONS

Size	Pattern	Ply Rating	Rim Width	Inflated Dimensions +/-2%		Load Capacity (Kg)	LP (Bar)
				OD (mm)	CSW (mm)		
3.00-18	43	6PR	1.85	625	81	200	2.80
110/90-16	43	6PR	2.50	598	110	243	2.25
100/90-17	38, 41, 42	6PR	2.50	612	101	218	2.25
100/90-18	38, 41, 42	6PR	2.50	641	102	224	2.25
120/80-17	44	6PR	2.75	626	121	257	2.30



THREE WHEELER- AUTO RICKSHAW TUK-TUK TYRES



GS 1



GS 1A



GS 2



GS 3



GS 4



GS 5



GS 6



GS 7



GS 8

***AVAILABLE IN VARIOUS PLY RATINGS AS PER INTERNATIONAL STANDARDS**

Size	Pattern	Ply Rating	Rim Width	Inflated Dimensions +/-2%		Load Capacity (Kg)	LP (Bar)
				OD (mm)	CSW (mm)		
4.00-8	1	8PR	3.00	425	110	400	4.25
4.00-8	1A	8PR	3.00	427	110	400	4.25
4.00-8	2 to 8	8PR	3.00	420	110	400	4.25



ULTRA LIGHT TRUCK TYRES



GS 3



GS 5



GS 13



GS 13A



GS 51



GS 52



GS 53



GS 54

***AVAILABLE IN VARIOUS PLY RATINGS AS PER INTERNATIONAL STANDARDS**

SPECIFICATIONS

Size	Pattern	Ply Rating	Rim Width	Inflated Dimensions +/-2%		Load Capacity (Kg)	LP (Bar)
				OD (mm)	CSW (mm)		
4.50-12	51	8PR 10PR	3.50	529	122	400 500	2.10
4.50-12	52	8PR 10PR	3.50	529	122	400 500	2.10
5.00-12	3, 13	8PR 10PR	3.50	516	134	590 640	5.00
5.00-12	13A	8PR 10PR	3.50	516	134	590 640	5.00
155/80 D12	5	8PR 10PR	4.50	546	151	550 600	4.50
155/80 D12	53	8PR 10PR	4.50	546	151	410 460	4.50
165/80 D13	54	8PR 10PR	4.50	597	165	670 720	4.50
165/80 D14	54	8PR 10PR	4.50	620	165	575 630	2.40

LIGHT TRUCK TYRES (LCV)



GS 3



GS 61



GS 62



GS 151



GS 152



GS 153



GS 154



GS 155



GS 156



GS 157



GS 158



GS 159



GS 160



GS 161

***AVAILABLE IN VARIOUS PLY RATINGS AS PER INTERNATIONAL STANDARDS**

SPECIFICATIONS

Size	Pattern	Ply Rating	Rim Width	Inflated Dimensions +/-2%		Load Capacity (Kg)	LP (Bar)
				OD (mm)	CSW (mm)		
7.00-15	151,152,153,154,155	12PR	5.50F	758	199	1175	6.20
7.50-15	156	14PR	6.00	780	211	1385	6.00
7.00-16	61, 3,151	16PR	6.00	813	211	1600	7.60
7.50-16	151, 157, 158, 159, 62, 160, 161	16PR	6.00	824	211	1600	7.60
8.25-16	151, 158, 159	16PR	6.50	863	234	1850	7.60

BUTYL INNER TUBES



SCOOTER / MOTORCYCLE TUBE SIZES

SIZE	ID	VALVE
3.50-8	GS-B1	V1-08-3
4.00-8	GS-B2	V1-08-3
2.75/3.00-10	GS-B3	V1-08-1
3.50-10	GS-B4	V1-08-1
4.50/5.00-10	GS-B5	TR-13
90/90-12	GS-B6	V1-08-1
4.50/5.00-12	GS-B7	TR-13
2.75/3.00-14	GS-B8	TR-29
2.25/2.50-16	GS-B9	TR-29
3.50-16	GS-B10	TR-29
110/90-16	GS-B11	TR-29
2.25/2.50-16	GS-B12	TR-29
3.50-16	GS-B13	TR-29
2.25/2.50-17	GS-B14	TR-29
2.75/3.00-17	GS-B15	TR-29
2.25/2.50-18	GS-B16	TR-29
2.75/3.00-18	GS-B17	TR-29
3.00/3.25-19	GS-B18	TR-29
100/90-17	GS-B19	TR-29
100/90-18	GS-B20	TR-29
90/90-18	GS-B21	TR-29
3.00/3.25-18	GS-B22	TR-29
3.50/4.10-18	GS-B23	TR-29

PASSENGER CAR TUBE SIZES

SIZE	ID	VALVE
4.00/4.50/5.65-12	GS-B24	TR-13
145/155R12	GS-B25	TR-13
145/155R13	GS-B26	TR-13
155/165R13	GS-B27	TR-13
165/175/185R13	GS-B28	TR-13
165/175R14	GS-B29	TR-13
600R14	GS-B30	TR-13
175/185R14	GS-B31	TR-13
6.50-14	GS-B32	TR-13
185/195R15	GS-B33	TR-13
195/205R15	GS-B34	TR-13
215/225R15	GS-B35	TR-13
225/70R15	GS-B36	TR-13
235/70R15	GS-B37	TR-13
255/70R15	GS-B38	TR-13
265/70R15	GS-B39	TR-13
5.90/6.40-15	GS-B40	TR-13
235/70R16	GS-B41	TR-13

ADV TUBE SIZES

SIZE	ID	VALVE
5.00-19	GS-B104	TR-14
6.00-19	GS-B105	TR-14
7.00-19	GS-B106	TR-14
8.00-19	GS-B107	TR-14

BUTYL INNER TYBES



LIGHT TRUCK TUBES (LCV) TUBE SIZES

SIZE	ID	VALVE
7.00/7.50R15	GS-B42	TR-75A
8.15/8.25R15	GS-B43	TR-75A
7.00-16/700R16	GS-B44	AB1582/TR-75A/TR15
7.50-16/700R16	GS-B45	AB1582/TR-75A/TR15
825R16	GS-B46	TR-77A

TRUCK & BUS TUBE SIZES

SIZE	ID	VALVE
6.50/7.50-20/750R20	GS-B47	TR-13/TR-15/TR-75A
8.25-20/825R20	GS-B48	TR-175A
9.00R20	GS-B49	TR-175A
10.00R20	GS-B50	TR-175A
11.00R20	GS-B51	TR-78A
12.00-20/1200R20	GS-B52	TR-78A
12.00R24	GS-B53	TR-78A/V030605

FORKLIFT / INDUSTRIAL TUBE SIZES

SIZE	ID	VALVE
4.00-8	GS-B86	JS2
5.00-8	GS-B87	JS2/TR-15
6.00-9	GS-B88	TR-75
6.50-10	GS-B89	TR-75
7.00-12	GS-B90	TR-75
7.50-10	GS-B91	TR-75
7.50-15	GS-B92	TR-75
8.25-15	GS-B93	TR-75
2.50-15	GS-B94	TR-75
3.00-15	GS-B95	TR-75
28x9-15	GS-B96	TR-75

OTR (OFF THE ROAD) TUBE SIZES

SIZE	ID	VALVE
13.00-24	GS-B97	TR-78A/TR-1175
14.00-24/25	GS-B98	TR-78A/TR-1175
15.5-25	GS-B99	TR-179/TR-1175
17.5-25	GS-B100	TR-1175
23.5-25	GS-B101	TR-1175
26.5-25	GS-B102	TR-1175
29.5-25	GS-B103	TR-1175

AGRICULTURAL TRACTOR SIZES

SIZE	ID	VALVE
6.00-12	GS-B54	TR-13
6.00-16	GS-B55	TR-13
6.50-16	GS-B56	TR-13
7.50-16	GS-B57	TR-15
9.00-16	GS-B58	TR-75
7.50-18	GS-B59	TR-15
10.00-16	GS-B60	TR-75
11.00-16	GS-B61	TR-75
11.2-24	GS-B62	TR-218A
9.5-24	GS-B63	TR-218A
12.2-24	GS-B64	TR-218A
14.9-24	GS-B65	TR-218A
16.9-24	GS-B66	TR-218A
12.4-28	GS-B67	TR-218A
13.6-28	GS-B68	TR-218A
14.9-28	GS-B69	TR-218A
16.9-28	GS-B70	TR-218A
16.9-30	GS-B71	TR-218A
18.4-26	GS-B72	TR-218A
18.4-30	GS-B73	TR-218A
18.4-34	GS-B74	TR-218A
15.5-38	GS-B75	TR-218A
20.8-38	GS-B76	TR-218A

AGRICULTURAL IMPLEMENT TUBE SIZES

SIZE	ID	VALVE
1000-15	GS-B77	TR-15
11L-15	GS-B78	TR-15
11L-15	GS-B79	TR-15
10.80-12	GS-B80	TR-75
10.0/75-15.3	GS-B81	TR-15
11.5/80-15.3	GS-B82	TR-15
12.5/80-15.3	GS-B83	TR-218A
12.5/80-18	GS-B84	TR-218A
13.065-18	GS-B85	TR-218A

GEESTONE



TYRES | INNER TUBES | PATCHES
ENVELOPS | FLAPS



GEESTONE TYRES CO.
(RAVI NANDAN & SONS)

Head Office:
Plot No.:171, Gill Road, Ludhiana (Punjab) INDIA
Ph: +91 161 4620957, M: +91 902 310 0110
E-mail: info@nandanworld.com
www.geestonetyres.com



Butyl Tube



MADE IN INDIA

